

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # 108
Sta Put® Ultra



MATERIAL SAFETY INFORMATION SERVICE

Hercules Chemical Company Inc.
 111 South Street
 Passaic NJ 07055
 Phone (800) 221-9330
 Fax (800) 333-3456

Date Prepared: 8/29/2005 Last Reviewed: 8/10/2006

Meets OSHA 29 CFR 1910.1200

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s), CAS Numbers)	OSHA PEL	ACGIH TLV	Other Limits	Upper Bound Limit if SARA Reportable
This product is not classified as hazardous in accordance with OSHA 1910.1200				N/A

HMIS Hazard Rating: Health: 1 Flammability: 0 Reactivity: 0 Personal Protection A

Section 3 - Physical/Chemical Characteristics

Boiling Point (°F):	Specific Gravity (H ₂ O = 1):	Vapor Density (Air = 1):	Vapor Pressure (mm Hg):
N/A	1.95	N/A	N/A
Melting Point (° F):	Evaporation Rate: (Butyl Acetate = 1)	Solubility in Water:	
N/A	N/A	Insoluble	
Appearance And Color:	Off white malleable putty	Odor:	Odorless

Section 4 - Fire And Explosion Hazard Data

Flash Point:	Flammable Limits:	LEL:	UEL:
N/A	N/A	N/A	N/A

Extinguishing Media: Dry chemical or carbon dioxide or water.

Special Firefighting Procedures:

Fire fighters must Wear MSHA/NIOSH approved positive pressure self-contained breathing apparatus with full face mask.

Unusual Fire And Explosion Hazards:

None, product non-flammable

Continued on Next Page

Section 5 - Reactivity Data

Stability: Stable **Conditions To Avoid:** None known

Incompatibility (Materials To Avoid): Strong oxidizers

Hazardous Decomposition: Carbon dioxide and carbon monoxide may be released on burning. May generate formaldehyde at temperatures greater than 150°C (300°F)

Hazardous Polymerization: Will Not Occur

Section 6 - Health Hazard Data

Routes of Entry: Inhalation N/A **Skin** Yes/Primary **Ingestion** Yes/Primary

Health Hazards:

Prolonged contact with skin or eyes may cause irritation. May cause stomach discomfort if ingested.

Carcinogenicity: **NTP** NO **IARC** NO **OSHA Regulated** NO

Signs And Symptoms of Exposure:

None

Medical Conditions Generally Aggravated By Exposure:

None known.

Emergency And First Aid Procedures:

EYES: Irrigate or flush eyes with water for 15 minutes, get medical attention if necessary. **SKIN:** Wash with soap and water. Seek medical attention if irritation develops. **INGESTION:** Not considered toxic but consuming large amounts may cause stomach discomfort or intestinal blockage.

Continued on Next Page

Section 7 - Precautions For Safe Handling And Use:**Steps To Be Taken In Case Material Is Released Or Spilled:**

Sweep Up

Waste Disposal Method:

Non-hazardous landfill

Precautions To Be Taken In Handling And Storing:

None normally required

Other Precautions:

None

Section 8 - Control Measures:**Respiratory Protection:**

None required for putty. If putty dries and dust is created dust-type respirator required.

Ventilation: Local Exhaust Adequate
Mechanical N/A**Special** N/A**Other:** N/A**Gloves:** Not normally required.**Eye Protection:** Advisable to wear safety glasses but none required.**Other Protective Clothing:** None**Work/Hygienic Practices** Always practice good hygiene by washing thoroughly after handling.**F**ACTS
axed
AST!

For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.